

## A1625B

# 8 Channel 1kV/25 - 2.5 mA Individual Floating Channel Dual Range Board



## Features



- 8 independently controllable High Voltage channels
- Output voltage:  $0 \div 1000$  V
- Dual range current:
  - High Power: 25 mA (100 nA monitor resolution)
  - High resolution: 2.5 mA (10 nA monitor resolution)
- Available with Negative / Positive / Mixed Polarity
- DB37 connectors
- **Floating Type:** Individual Floating
- Low ripple
- Under/over-voltage alert, overcurrent and max. voltage protection
- Interlock logic for unit enable
- Software Tools for easy channel management

## Description

The CAEN Mod A1625B is a single width board (5 TE wide) that houses 8 independent high voltage channels.

All channels have independent floating returns, isolated up to 50 V from each other and from chassis/crate ground (Individual Floating channel) The board is available with positive, negative or mixed output polarity. Channels are delivered with **DB37** connectors. Consult our **connectors reference page** for technical information.

The output voltage range is **0 ÷ 1000 V**, with **20 mV** monitor resolution. The output channels offer **dual current ranges** (software selectable):

<b>High Power:</b> 0 ÷ 25 mA	<b>High Resolution:</b> 0 ÷ 2.5 mA
I set resolution: 500 nA	I set resolution: 500 nA
I mon resolution: 100 nA	I mon resolution: 10 nA

Independently programmable for each channel:

<b>Output voltage:</b>	0 ÷ 1000 V	Step: 20 mV
<b>Current limit (Iset):</b>	0 ÷ 25 / 2.5 mA selectable	Step: 500 nA
<b>V Ramp up/down:</b>	1 ÷ 100 V/s	Step: 1 V/s
<b>TRIP parameter:</b>	0 ÷ 999.9 s; 1000 s = Infinite	Step: 0.1 s

Safety features include:

- **Channels:** can be enabled or disabled through the Global Interlock logic.
- **Overvoltage and Undervoltage warning:** when the output voltage differs from the programmed value.
- **Overcurrent detection:**
- **Hardware VMAX:** maximum output voltage can be set, via front panel potentiometer, at the same common value for all the board channels. VMAX value can be read out via software.
- **Safety Board Interlock:** this protection allows to disable the primary HV generation when the HV outputs are not connected to their loads.

CAEN provides a complete software range to control, monitor and configure its Power Supply products.

- **GECO2020 General Control Software**
- **CAEN HV Wrapper Library**
- **HiVoCS web tool**
- **OPC Server for CAEN Power Supplies**
- **EPICS Service**

These tools, which support the most used operating systems, ranging from low level libraries (**CAEN HV Wrapper Library**), to be used as a source for customer designed software, to the WEB interface (**HIVOCS**) available on each mainframe, up to the all-inclusive Control Software (**GECO2020**) with user friendly graphical interfaces, to meet any application needs.

Advanced control via OPC Server (**CAEN OPC Server**) and EPICS (**EPICS IOC**) is supported, to easily include CAEN power supplies within existing setups featuring such standards.

- **All tools are available for free download.**

### Universal Multichannel Power Supply Systems (Mainframes)

Universal Multichannel Power Supply Systems, or Mainframes, are modular systems designed to house and control High Voltage (HV) and Low Voltage (LV) boards, providing power for particle detectors and their associated electronics in standard 19" racks. CAEN offers four mainframe versions:

- **SY4527:** A large experimental system. This 19" wide / 8U high mainframe can house **up to 16 HV/LV boards**. It offers a power output from 600W up to a maximum of **4200W**, depending on installed Power

Supply Units and display type. Local control is optionally available via a 10.4" or 5.7" LCD Touchscreen.

- **SY5527:** A more compact laboratory version. This 19" wide / 4U high mainframe can house **up to 6 HV/LV boards**. Its power output ranges from 600W up to a maximum of **1800W**, depending on Power Supply Units. Optional local control is available via a 5.7" LCD Touchscreen.
- **SY4527LC:** A cost-effective alternative with a shorter depth (~20cm compared to standard SYx527). This 19" wide / 8U high mainframe houses **up to 10 boards** and includes a **600W power supply**. It does not include an LCD display. It is fully compatible with SY4527 and SY5527 boards.
- **SY5527LC:** Also a cost-effective, shorter depth alternative (~20cm compared to standard SYx527). This 19" wide / 4U high mainframe houses **up to 4 boards** and includes a **400W power supply**. It does not include an LCD display. It is fully compatible with SY4527 and SY5527 boards.

All systems offer modular design for simplified upgrades and maintenance and can be controlled remotely via Ethernet.

## Ordering Options

Code	Description	
WA1625BMXAAA	A1625BM - SYx527 mixed polarity individual floating 8 ch 1000 V/25-2.5 mA (20 W) board	RoHS
WA1625BNXAAA	A1625BN - SYx527 negative individual floating 8 ch 1000 V/25-2.5 mA (20 W) board	RoHS
WA1625BPXAAA	A1625BP - SYx527 positive individual floating 8 ch 1000 V/25-2.5 mA (20 W) board	RoHS



**This document, or parts thereof, may not be reproduced in any form or by any means without written permission from Caen S.p.A. Although every effort has been made to ensure the accuracy of information presented in this catalog, Caen S.p.A reserves the right to modify its products specifications without giving any notice; for up to date information please visit [www.caen.it](http://www.caen.it) © Caen S.p.A - 2024**

**CAEN S.p.A.**

Via Vetraia 11  
55049 - Viareggio  
Italy

**Phone +39.0584.388.398**

**Fax +39.0584.388.959**

**info@caen.it**

**www.caen.it**

**CAEN GmbH**

Brunnenweg 9  
64331 Weiterstadt, Germany

**Phone +49 (0)212.254.4077**

**Mobile +49 (0)151.16.548.484**

**info@caen-de.com**

**www.caen-de.com**

**CAEN Technologies, Inc.**

1 Edgewater Street - Suite 101  
Staten Island, NY 10305  
USA

**Phone +1.718.981.0401**

**Fax +1.718.556.9185**

**info@caentechnologies.com**

**www.caentechnologies.com**

**CAENspa India Private Limited**

B205, BLDG42, B Wing,  
Azad Nagar Sangam CHS,  
Mhada Layout, Azad Nagar, Andheri West  
Mumbai, Maharashtra 400053, India

**info@caen-india.in**

**www.caen-india.in**

