

A7236

12/24/32 Channel 3.5 kV, 1.5/0.15 mA (4W) Common Floating Return Dual Range Boards



Features



- 12 / 24 / 32 independently controllable High Voltage channels
- Maximum output voltage: 3500 V
- Dual range current:
 - High Power: 1.5 mA (5 nA monitor resolution)
 - High resolution: 0.15 mA (0.5 nA monitor resolution)
- Available with Negative / Positive Polarity
- Radial 52 / REDEL 51 / SHV connectors
- **Floating Type:** Common Floating Return
- Low ripple
- Under/over-voltage alert, overcurrent and max. voltage protection
- Interlock logic for unit enable
- Software Tool for easy channel management

Description

The power supplies of the A7236 Family house 12 / 24 / 32 independent high voltage channels.

The channels share a Common Floating Return, which is insulated from the chassis/crate ground. This feature may help to minimize problems of ground-loops. The board is available with positive or negative output polarity Channels are delivered with Radiall 52 / REDEL 51 / SHV connectors. Consult our **connectors reference page** for technical information.

The output voltage range is **0 ÷ 3500 V**, with **5 mV** monitor resolution. The output channels offer **dual current ranges** (software selectable):

High Power: 0 ÷ 1.5 mA	High Resolution: 0 ÷ 0.15 mA
I set resolution: 10 nA	I set resolution: 10 nA
I mon resolution: 5 nA	I mon resolution: 0.5 nA

Independently programmable for each channel:

Output voltage:	0 ÷ 3500 V	Step: 5 V
Current limit (Iset):	0 ÷ 1.5 / 0.15 mA selectable	Step: 10 nA
V Ramp up/down:	1 ÷ 500 V/s	Step: 1 V/sec
TRIP parameter:	0 ÷ 999.9 s; 1000 s = Infinite	Step: 0.1 s

Safety features include:

- **Channels:** can be enabled or disabled through the Global Interlock logic.
- **Overvoltage and Undervoltage warning:** when the output voltage differs from the programmed value.
- **Overcurrent detection:** when a channel attempts to exceed the programmed current limit, it signals an "overcurrent" condition and enters TRIP status. The output voltage is adjusted to keep the current below the programmed limit for a programmable TRIP time, after which the channel is switched off. If TRIP is set to "constant current mode", the channel behaves as a current source.
- **Hardware VMAX and IMAX:** maximum output voltage and maximum current value can be fixed, via front panel potentiometer, at the same common value for all the board channels. IMAX and VMAX values can be read out via software.
- **Safety Board Interlock:** this protection disables the HV generation when the HV outputs are not connected to their loads (only for Multipin Connector versions).

To create cables compatible with versions equipped with Radiall 52 connectors, CAEN provides two accessories: the Mate cable connector (Model A996) and the corresponding insertion/extraction tool (Model A995).

CAEN provides a complete software range to control, monitor and configure its Power Supply products.

- **GECO2020 General Control Software**
- **CAEN HV Wrapper Library**
- **HiVoCS web tool**
- **OPC Server for CAEN Power Supplies**
- **EPICS Service**

These tools, which support the most used operating systems, ranging from low level libraries (**CAEN HV Wrapper Library**), to be used as a source for customer designed software, to the WEB interface (**HIVOCS**) available on each mainframe, up to the all-inclusive Control Software (**GECO2020**) with user friendly graphical interfaces, to meet any application needs.

Advanced control via OPC Server (**CAEN OPC Server**) and EPICS (**EPICS IOC**) is supported, to easily include CAEN power supplies within existing setups featuring such standards.

- **All tools are available for free download.**

Universal Multichannel Power Supply Systems (Mainframes)

Universal Multichannel Power Supply Systems, or Mainframes, are modular systems designed to house and control High Voltage (HV) and Low Voltage (LV) boards, providing power for particle detectors and their associated electronics in standard 19" racks. CAEN offers four mainframe versions:

- **SY4527:** A large experimental system. This 19" wide / 8U high mainframe can house **up to 16 HV/LV boards**. It offers a power output from 600W up to a maximum of **4200W**, depending on installed Power Supply Units and display type. Local control is optionally available via a 10.4" or 5.7" LCD Touchscreen.
- **SY5527:** A more compact laboratory version. This 19" wide / 4U high mainframe can house **up to 6 HV/LV boards**. Its power output ranges from 600W up to a maximum of **1800W**, depending on Power Supply Units. Optional local control is available via a 5.7" LCD Touchscreen.
- **SY4527LC:** A cost-effective alternative with a shorter depth (~20cm compared to standard SYx527). This 19" wide / 8U high mainframe houses **up to 10 boards** and includes a **600W power supply**. It does not include an LCD display. It is fully compatible with SY4527 and SY5527 boards.
- **SY5527LC:** Also a cost-effective, shorter depth alternative (~20cm compared to standard SYx527). This 19" wide / 4U high mainframe houses **up to 4 boards** and includes a **400W power supply**. It does not include an LCD display. It is fully compatible with SY4527 and SY5527 boards.

All systems offer modular design for simplified upgrades and maintenance and can be controlled remotely via Ethernet.

Technical Specifications

No. of Channels

12, 24 or 32 (Common Floating Return)

Output Voltage

0÷3.5 kV

Polarity

Positive / Negative depending on purchased version

Max. Output Current

Dual range:

- High Power: 1.5 mA
- High Resolution: 150 μ A

Voltage Set Resolution

5 mV

Voltage Monitor Resolution

5 mV

Current Set Resolution

10 nA

Current Monitor Resolution

- High Power: 5 nA
- High Resolution: 500 pA

VMAX hardware

0÷3.5 kV common for all the board channels

VMAX hardware accuracy

\pm 1% of FSR

VMAX software

0÷3.5 kV settable for each channel

VMAX software resolution

1 V

IMAX hardware

0÷1.5 mA common for all the board channels

IMAX hardware accuracy

\pm 1% of FSR

Ramp Up/Down

1 ÷ 500 Volt/sec, 1 Volt/sec step settable for each channel

Voltage Ripple

- 10 ÷ 1000 Hz: <12 mVpp (typ); < 15 mVpp (max)
- 1 ÷ 20000 kHz: <6 mVpp (typ); < 10 mVpp (max)

Voltage Monitor vs. Output Voltage Accuracy

typical: $\pm 0.3\% \pm 0.2 \text{ V}$ max: $\pm 0.3\% \pm 1 \text{ V}$

Voltage Set vs. Output Voltage Accuracy

typical: $\pm 0.3\% \pm 0.2 \text{ V}$ max: $\pm 0.3\% \pm 1 \text{ V}$

Current Monitor vs. Output Current Accuracy

- High Power: typical: $\pm 1\% \pm 200 \text{ nA}$; max: $\pm 1\% \pm 2 \mu\text{A}$
- High Resolution: typical: $\pm 1\% \pm 100 \text{ nA}$; max: $\pm 1\% \pm 1 \mu\text{A}$

Current Set vs. Output Current Accuracy

- High Power: typical: $\pm 1\% \pm 200 \text{ nA}$; max: $\pm 1\% \pm 2 \mu\text{A}$
- High Resolution: typical: $\pm 1\% \pm 100 \text{ nA}$; max: $\pm 1\% \pm 1 \mu\text{A}$

Maximum output power

4 W per channel (software safety limit)

Consumption @ full power

- 32 channels (A7236): 185 W
- 24 channels (A7236S): 145 W
- 12 channels (A7236D): 80 W

Ordering Options

Code	Description	
WA7236DNXAA1	A7236DN - SYx527 H.V. channels -3.5KV 1.5mA (4W) - SHV Conn. common floating (12ch)	RoHS
WA7236DPXAA1	A7236DP - SYx527 H.V. channels +3.5KV 1.5mA (4W) - SHV Conn. common floating (12ch)	RoHS
WA7236NXAAA3	A7236N - SYx527 H.V. channels -3.5KV 1.5mA (4W) -Multipin Conn. common floating (32ch)	RoHS
WA7236NXAAR3	A7236NR - SYx527 H.V. channels -3.5KV 1.5mA (4W) - Redel Conn. common floating (32ch)	RoHS
WA7236PXAAA3	A7236P - SYx527 H.V. channels +3.5KV 1.5mA (4W) -Multipin Conn. common floating (32ch)	RoHS
WA7236PXAAR3	A7236PR - SYx527 H.V. channels +3.5KV 1.5mA (4W) - Redel Conn. common floating (32ch)	RoHS
WA7236SNXAA2	A7236SN - SYx527 H.V. channels -3.5KV 1.5mA (4W) - SHV Conn. common floating (24ch, 10TE)	RoHS
WA7236SPXAA2	A7236SP - SYx527 H.V. channels +3.5KV 1.5mA (4W) - SHV Conn. common floating (24ch, 10TE)	RoHS

Accessories

R649B



32 Channel Multipin Radial to SHV connector Adapter (Max: 8 kV - 19' Rack)

A995



Insertion/extraction tool for A996

A649




32 Channel Multipin Radial to SHV connector Adapter (Max: 3 kV - Desktop)

HV CABLES



High Voltage Cable Assemblies

A996



52 pin cable connector

A649B



32 Channel Multipin Radial to SHV connector Adapter (Max: 8kV - Desktop)

R649



32 Channel Radial to SHV connector Adapter (Max: 3 kV - 19' Rack)

Related Products

SY4527



Universal Multichannel Power Supply System / 19"wide, 8U-high (16 slot)

SY5527



Universal Multichannel Power Supply System / 19"wide, 4U-high (6 slot)

SY5527LC



Universal Multichannel Power Supply System Low Cost / 19"wide, 4U-high (4 slot)

SY4527LC



Universal Multichannel Power Supply System Low Cost / 19"wide, 8U-high (10 slot)

Gallery



A7236 Family: 12/24/32 Channel 3.5 kV, 1.5/0.15 mA (4W) Common Floating Return Dual Range Boards, available with Negative / Positive Polarity, SHV / Radiall 52 /REDEL 51 connectors



Single width (5 TE wide), 32 channel: A7236N, A7236P



Double width (10 TE wide), 24 channels: A7236SN, A7236SP



Single width (5 TE wide), 12 channels: A7236DP, A7236DN



Radiall multipin connector. (Factory Name: Radiall 691 803 004)



SHV connector. (Factory Name: Radiall R317580)



REDEL multipin connector (Factory Name: SLG.H51.LLZG)

This document, or parts thereof, may not be reproduced in any form or by any means without written permission from Caen S.p.A. Although every effort has been made to ensure the accuracy of information presented in this catalog, Caen S.p.A reserves the right to modify its products specifications without giving any notice; for up to date information please visit www.caen.it © Caen S.p.A - 2024

CAEN S.p.A.

Via Vetraia 11
55049 - Viareggio
Italy

Phone +39.0584.388.398

Fax +39.0584.388.959

info@caen.it

www.caen.it

CAEN GmbH

Brunnenweg 9
64331 Weiterstadt, Germany

Phone +49 (0)212.254.4077

Mobile +49 (0)151.16.548.484

info@caen-de.com

www.caen-de.com

CAEN Technologies, Inc.

1 Edgewater Street - Suite 101
Staten Island, NY 10305
USA

Phone +1.718.981.0401

Fax +1.718.556.9185

info@caentechnologies.com

www.caentechnologies.com

CAENspa India Private Limited

B205, BLDG42, B Wing,
Azad Nagar Sangam CHS,
Mhada Layout, Azad Nagar, Andheri West
Mumbai, Maharashtra 400053, India

info@caen-india.in

www.caen-india.in

