

## **EASY3000S**

### **Front Access Crate for EASY3000 System for Hostile Area**



## Features



- Full integration in SY1527/SY2527 Systems
- Up to 10 boards per crate
- Up to 3 kW output power
- Magnetic field tolerance up to 2 kGauss
- Radiation tolerance
- Front panel power supply and link connection

## Description

**EASY3000 (Embedded Assembly SYstem)** is the new CAEN power supply solution for operation in magnetic **field and radioactive environment**. CAEN has been involved for more than a decade in developing different solutions for the main LHC experiments, where the electronic equipment of the experiment is dealing with high dose radiation and intense magnetic field. In order to provide safe and reliable operations in such hostile areas, CAEN started tests with rad-tolerant components and magnetic field resistant solutions, patenting the new technology that is now used in this new line of products.

### **APP PC5933T connector**

Vertical contact MINI P/CLAW APP PC5933T type for EASY3000S

Consult our **connectors reference page** for technical information.

Moreover, though designed for harsh environment, the EASY3000 modules can work also in normal condition with excellent performance. The **EASY3000S** crate is designed to house Power Supply and ADC boards of EASY3000 family; it supports mechanically EASY boards and distributes control signals and power supplies. It is handled by one of six branches of the **Branch Controller A1676A**.

The EASY3000S crate must be used with an air and/or water intercooler and its standard width fit the rack mounting. An optional fan tray (A3000F - EASY3000 Fan Unit) can be used for the stand-alone operation of the EASY3000S crate when no magnetic field is present.

EASY3000S is powered by external 48 V DC. The EASY architecture foresees two independent 48 V power supplies: the first (48 V Power) to power the channels regulators, the other (48 V Service) to power the control logic. EASY3000S has power supply and link connection on the front panel.

The use of CAEN 48 V power sources (Mod. **A3484**, **A3485** and **A3486**), allows to integrate into the channels control also the management of the 48 V power supplies; A3486 is also suitable to hostile areas.

## Technical Specifications

### Nr. of modules per Crate (max)

10

### Depth

65 cm

### Height

6 U

### Width

19" (84 T.E.)

### Weight

11kg

## Ordering Options

Code	Description
WEASY3000MBS	EASY3000S - Crate for EASY3000 PowerSupply System in Hostile Area - Frontal Access

## Related Products

### EASY3000



Crate for EASY3000 Power Supply System for Hostile Area

---

### EASY3000B



Crate for EASY3000 System for Hostile Area with Bolt Connectors

---



**This document, or parts thereof, may not be reproduced in any form or by any means without written permission from Caen S.p.A. Although every effort has been made to ensure the accuracy of information presented in this catalog, Caen S.p.A reserves the right to modify its products specifications without giving any notice; for up to date information please visit [www.caen.it](http://www.caen.it) © Caen S.p.A - 2024**

**CAEN S.p.A.**

Via Vetraia 11  
55049 - Viareggio  
Italy

**Phone +39.0584.388.398**

**Fax +39.0584.388.959**

**info@caen.it**

**www.caen.it**

**CAEN GmbH**

Brunnenweg 9  
64331 Weiterstadt, Germany

**Phone +49 (0)212.254.4077**

**Mobile +49 (0)151.16.548.484**

**info@caen-de.com**

**www.caen-de.com**

**CAEN Technologies, Inc.**

1 Edgewater Street - Suite 101  
Staten Island, NY 10305  
USA

**Phone +1.718.981.0401**

**Fax +1.718.556.9185**

**info@caentechnologies.com**

**www.caentechnologies.com**

**CAENspa India Private Limited**

B205, BLDG42, B Wing,  
Azad Nagar Sangam CHS,  
Mhada Layout, Azad Nagar, Andheri West  
Mumbai, Maharashtra 400053, India

**info@caen-india.in**

**www.caen-india.in**

