A7508

1 Ch 800 V/50 µA High Efficiency HV Power Supply Module (5V in)

1	800 V	50 µA
No. of Channels	Max Output V	Max Output I

The A7508 is a compact, PCB-mount, single-channel high-voltage DC/DC converter providing a programmable and monitorable 0 to 800 V output from a +5 V input. Available with positive or negative polarity, it delivers up to 50 µA and uses external 0 to +2 V Vset and Iset controls for voltage and current regulation. Over-current protection limits the output and prevents damage. The low-noise module measures 29x54x16 mm3 (WxLxH) and is housed in a coated FR4 PCB assembly within a DC01 steel box.

Overview

Product Highlights

- High efficiency
- 800 V/50 µA output ranges
- Available with positive or negative polarity
- Compact package: 29x54x16 mm^3 (WxLxH)

Product Description

AT A GLANCE	
No. of Channels	**1**
Max Output V	**800 V**
Max Output I	**50 µA**
Vset Input (V)	**0 ÷ +2.5**
Vmon Output (V)	**0 ÷ +2.5**
Imon Output (V)	**0 ÷ +2.5**

The **A7508** is a high efficiency, low noise single channel High Voltage DC/DC converters in a PCB mount form factor. It provides a programmable and monitorable output voltage ranging from **0** to **800 V**, when supplied with a **+5 V** input. It is available with either positive or negative output voltage. The output voltage is regulated by providing a **0** to **+2 V** external voltage (Vset). The maximum output current is **50 µA**, regulated by providing **0** to **+2 V** external voltage (Iset). The board is provided with an over-current protection: if a current larger than the Iout maximum value is drawn, the module is not being damaged.

Thanks to its excellent stability and special design, **A7508** power supply is engineered to work in **harsh environment and under severe temperature variations**.

The module is engineered on a **FR4 PCB**, coated and housed in **DC01 steel box**. CAD Altium library components and 3D step models are available on request.

Safety Features Include:

- Overcurrent detection if the channel attempts to draw a current larger than Iset, the output voltage is varied to keep the current below Iset limit. The channel behaves like a current generator.

 — © 2026 CAEN S.p.A. All rights reserved. Specifications are subject to change without notice.

Technical Specifications

Packaging	Material: DC01; dimension: W=29 mm ; L=54 mm ; H=16 mm
Number of Channels	1
Maximum Output Current (Iout)	50 µA at ±800 V
Output Voltage (Vout)	0 ÷ 800 V
Contact pins	Male strip header; 2.54mm step; phosphor bronze; UL94V0 insulator
Protection	Over current, short circuit, sparks and humidity
Operating temperature	-40° C ÷ +70° C
Storage temperature	-55° C ÷ +85° C
Output Ripple (Full Load)	Typical < 3 mVpp, Maximum < 5 mVpp
Efficiency	~ 50% @ Vout = 800 V (-45° C ÷ +70° C)
Vout / Temperature coefficient	< 50 ppm / °C
DeltaVout/Vout (for ±5% Vin variations)	<1.5 X 10-3 @ full scale
Vout vs. Vset Integral Non Linearity	<±0.3% (-60° C ÷ +60° C)
Vmon vs. Vout Integral Non Linearity	<±0.3% (-60° C ÷ +60° C)
Uniformity of a lot	< 1 %
Voltage Supply (Vin)	+5 V ± 5%
Enable	Enable > 3.5 V Channel active Enable < 1 V Channel disabled
Vset Input (positive analog command)	0 ÷ +2 V Important!: Vset must not exceed 2 V (Vout is not limited)
Vmon Output (positive analog command)	0 ÷ +2 V
Iset input (positive analog command)	0 ÷ +2 V
Imon Output (positive analog command)	0 ÷ +2 V
Status OVC bit	0÷5 V (High = OVC)
Electromagnetic compatibility	Weak emission of electromagnetic impulse and RF; one-piece metal shielding with several ground connections
Power requirement	< 100 mW; @ 800 V / 50 µA (Rload ≈ 17 MOhm)
Thermal stability (DeltaVout/Vout)	< 50 ppm / °C

 — © 2026 CAEN S.p.A. All rights reserved. Specifications are subject to change without notice.

Ordering Information

ORDERING CODE	DESCRIPTION
WA7508NXAAAA	A7508N -800V 50µA HV Power Supply Module (5V in)
WA7508PXAAAA	A7508P +800V 50µA HV Power Supply Module (5V in)

1. Ordering codes and descriptions are reproduced from the product record. Availability is confirmed at order entry.

Accessories

DT75XX — HV Carrier Board for A750x PCB Modules

Related Products

A7501 — 1 Ch 2100 V/100 µA High Efficiency HV Power Supply Module

A7502 — 1 Ch 2100 V/100 µA High Efficiency HV Power Supply Module (5V in)

A7504C — 1 Ch 4 kV/100 µA High Efficiency HV Power Supply Module

A7505 — 1 Ch 1600 V/500 µA High Efficiency HV Power Supply Module

A7511 — 1 Ch 1100 V/1000 µA High Efficiency HV Power Supply Module

A7526 — 1 Ch 2600 V/500 µA High Efficiency HV Power Supply Module - PCB Mount

 — © 2026 CAEN S.p.A. All rights reserved. Specifications are subject to change without notice.