DT1419ET

4 Ch Reversible 500 V/200 µA Desktop HV Power Supply Module (USB/Ethernet/T.screen)

4	±500 V	200 µA
No. of Channels	Max Output V	Max Output I

The DT1419ET is a 4-channel reversible desktop high-voltage power supply module, delivering up to ±500 V and 200 µA per channel from 110/220 V AC. Each channel has independently selectable polarity, 1–50 V/s ramp-up and ramp-down rates, and SHV output through Radiall R317580 connectors. It provides 5 nA Iset/Imon resolution, expandable to 500 pA with x10 Imon Zoom, plus a common floating return. Local control uses a 2.8″ color touchscreen; USB 2.0 and Ethernet support remote operation. Interlock, channel kill, TRIP and programmable VMAX protection are included.

CAEN
Tools for Discovery

Overview

Product Highlights

- 4 independent channels in a Desktop case (110/220V AC Powered)
- Channels with individually selectable positive or negative polarity
- Common floating return
- Under/over-voltage alert, overcurrent and max. voltage protection
- 5 nA Current monitor resolution (with x10 Imon-Zoom: 500 pA)
- Local and Remote control (USB2.0/Ethernet)
- Software Tools for easy channel management
- 500 V / 200µA output range
- SHV coaxial output connectors
- Low Ripple
- Interlock logic for board enable and Individual channel kill
- 2.8″ color touch screen display
- Daisy-chain capabilty

Product Description

AT A GLANCE	
No. of Channels	**4**
Max Output V	**±500 V**
Max Output I	**200 µA**
Vset/Vmon Resolution	**10 mV**
Iset/Imon Resolution	**Iset: 5 nA Imon: 5 / 0.5 nA**
Max. Ramp Up/Down Rate	**100 V/s**

The CAEN **Mod. DT1419ET** provides **4** independent high voltage channels in a desktop package (110/220 V AC powered). Each channel delivers up to **±500 V** and **200 µA**, and its output polarity can be selected independently.

The channels share a common floating return, insulated from the crate ground, and the HV outputs are delivered through Radiall R317580 SHV coaxial connectors; for further technical information, consult our connectors reference page. Ramp-up and ramp-down rates can be set independently for each channel from 1 to 50 V/s in 1 V/s steps. The module offers 5 nA Iset/Imon resolution, and the x10 Imon Zoom increases the current monitor resolution to 500 pA.

The module can be controlled **locally**, through a **2.8″ color touchscreen LCD display** with a completely redesigned user interface, or **remotely** via **USB 2.0** or **Ethernet**.

A complete set of **free software tools** is available to control the unit: GECO2020, with a user-friendly GUI, and the CAEN HV Wrapper library for custom software development. EPICS and LabVIEW are also supported.

 — © 2026 CAEN S.p.A. All rights reserved. Specifications are subject to change without notice.

Overview (continued)

The module also includes dedicated safety features that allow it to operate as a current generator. A common safety board interlock logic enables or disables the channels globally, while individual input signals provide a kill function for each channel. An overvoltage and undervoltage warning is issued when the output voltage differs from the programmed value by more than 2% of the set value (minimum 10 V). If a channel attempts to draw a current higher than its programmed limit, it enters TRIP status and holds the maximum allowed value for a programmable time (TRIP) before being switched off. A programmable hardware VMAX protection limit is also available.

Technical Specifications

Package	• Desktop module housed in a 239x84x184 mm3 (WxHxD) Aluminium case • Weight: ~5.2 kg
Output channels	• 4 channels, Common Floating Return, SHV connector • Positive or Negative Polarity (requires internal setting)
Output ranges	500 V / 200µA
Max. Ch. Output Power	0.1W
Vset Resolution	10 mV
Vmon Resolution	10 mV
Iset Resolution	5 nA
Imon Resolution	5 nA (IMonRange = High) 500 pA (IMonRange = Low) – Imon Zoom Active
Vmax	• 0 ÷ 510 V Absolute maximum HV level that the channel is allowed to reach, independently from the preset value Vset. • Output voltage cannot exceed the preset value Vmax. The accuracy is 1 % ± 0.5 V
Vmax resolution	± 0.1 V
Alarm output	Open collector, 100 mA maximum sink current
Interlock input	LOW: <1V; current~5mA; HIGH: 4÷6 V
Ramp Up/Down	1÷50 Volt/s, 1 Volt/s step

Trip

- Max. time an “overcurrent” can last (seconds). A channel in “overcurrent” works as a current generator; output voltage varies in order to keep the output current lower than the programmed value.
- “Overcurrent” lasting more than set value (1 to 9999) causes the channel to “trip”.
- Output voltage will drop to zero either at the Ramp-down rate or at the fastest available rate, depending on Power Down setting; in both cases the channel is put in the OFF state.
- Trip range: 0 ÷ 999.9 s; 1000 s = INFINITE. Step = 0.1 s (If trip= INFINITE, “overcurrent” lasts indefinitely)

 — © 2026 CAEN S.p.A. All rights reserved. Specifications are subject to change without notice.

Technical Specifications (continued)

Voltage Ripple	• 20 ÷ 1000 Hz: Typical: 5 mVpp / Maximum: 10 mVpp • 1 ÷ 20000 kHz: Typical: 3 mVpp / Maximum: 5 mVpp
Vmon vs. Vout Accuracy	±0.02% of read value ±0.2V
Vset vs. Vout Accuracy	±0.02% of set value ±0.2V
Imon vs. Iout Accuracy	±2% of read ±20 nA (IMonRange = High) ±2% of read ±2 nA (IMonRange = Low)
Iset vs. Iout Accuracy	±2% of read ±30 nA (IMonRange = High) ±2% of read ±3 nA (IMonRange = Low)
Ventilation Fan	60 x 60 24 V; 62 dBA maximum noise level
Humidity range	0 ÷ 80%
Storage temperature	-10 ÷ 70°C
Operating temperature	0 ÷ 45°C
Vout / Temperature coefficient	max. 50 ppm / °C
Imon / Temperature coefficient	max 100 ppm / C°; max 300 ppm / C° with Imon zoom
Long term stability Vout vs. Vset	± 0.02% (after one week @ constant temperature)

Ordering Information

ORDERING CODE	DESCRIPTION
WDT1419ETXAA	DT1419ET – 4 Channel 500V/200uA Desktop HV PowerSupply Module with Ethernet & 2.8″ Touchscreen

1. Ordering codes and descriptions are reproduced from the product record. Availability is confirmed at order entry.

Accessories

A148x — Inhibit - Kill Signal BNC Adapter for HV Power Supply Modules

HV CABLES — High Voltage Cable Assemblies

Software & Control Tools

EPICS IOC (PSM Power Supply Modules) — EPICS IOC for Power Supply Modules

GECO2020 — GEneral COntrol Software for CAEN HV Power Supplies

LabVIEW Driver (PSM – Power Supply Modules) — LabVIEW Instrument Driver for Power Supply Modules

 — © 2026 CAEN S.p.A. All rights reserved. Specifications are subject to change without notice.